



LOAD WEIGHING DEVICE SYSTEM LOAD CELLS & UNIT CONTROL

ELEVATORS/ FREIGHT ELEVATORS

Dinacell electrónica, S. L.

Pol. Ind. Santa Ana. C/ El Torno, 8.


28529 Rivas Vaciamadrid (Madrid) - Spain

Phone: (34) 91 300 14 35 - Fax: (34) 91 300 16 45

E-mail: dinacell@dinacell.com - www.dinacell.com

Inprime: DINICOLOR, S.L. D.L.: M-

The weighing system in the elevator




TCA 800

- Load cell for installation under cabin base.
- Mounted on the silent-block pad to avoid the transfer of vibrations.
- Connected to the unit control of the series VK, and can able to install a quantity of 8 cells in parallel.
- They are manufactured in 2 different kinds:
 - Individual Model TCA-800/I
 - Model in Group TCA-800/G (800x4=3.200 kg), where the four cells are active and it facilitates the electrical connection.
- "Auto-calibrated" No need to introduce a well-known weight in side the cabin for the adjustment.
- Model of maximum precision. It is recommended for the installation of new elevators.




Technical Characteristic

Sensibility	2 (mV/V) \pm 1%
Tension of excitement	5...10V (max. 15V)
Temperatura range of work	-20 a +70 °C
Non linearity	<0.15 % F.E.
Non repeatability	<0.15 % F.E.
Hysteresis	<0.05 % F.E.
Combined error	<0.2 % F.E.
Input resistance	>1000 Ω
Output resistance	1000 Ω \pm 2
Insulation resistance (V. Test =100V)	>5.000x10 ⁶ Ω
Maximum work load	150 % F.E.
Load limit without lost of characteristic	200 % F.E.



Dimensions in mm.
A=M-10 or M-12

Load cells in group



Individual load cell





Diagram of Installation



LCK

- Load limiter with integrated circuits, of great precision and stability for the measurement of the load in steel cables.
- Auto-calibrated". No need to introduce a well-known weight in cabin for their adjustment.
- Special software for chain compensation.
- It carry a "comprise clamp" for the limitation of weight in elevators and freight elevators.

Capacities


4.000 kg

6.000 kg





Technical Characteristic

Full scale	2.500 kg ± 5%
Non linearity	<0.15 % F.E.
Non repeatability	<0.15 % F.E.
Hysteresis	<0.05 % F.E.
Combined error	<0.2 % F.E.
Insulation resistance.... (V. Test =100V).	>5.000x10 ⁶ Ω
Maximum work load.	150 % F.E.
Load limit without lost of characteristic	200 % F.E.




Dimensions in mm.




Cabin Display


- Progressive indicator of the load.
- The model MBL has also an integrated emergency light.
- Visual indicator of the full load.
- Visual and Sound indicator of the overload.
- Front panel made of stainless steel.
- Installation in frame panel, evened or with mark.
- 2 wires connections without polarity.



MBD



MBL



MBR

Note: For other designs and special measures, please contact our commercial department.

LOAD CELLS TCA , TCE , SW , LCA , LCK , BPP , BPP-CB , BPP-LR , BPH
SENSORES SW-GAMA , SW-OMEGA , SW-OMEGA PLUS , CABIN DISPLAY
MB , EQUIPOS VK-3 , VK-2T , VK-2C , VK-3I , VK-OMEGA , VK-OMEGA-
PLUS , VKL , ADS-420 , LOAD CELLS TCA , TCE , SW , LCA , LCK , BPP ,
BPP-CB , BPP-LR , BPH , SENSORES SW-GAMA , SW-OMEGA , SW-OMEGA
PLUS , CABIN DISPLAY MB , EQUIPOS VK-3 , VK-2T , VK-2C , VK-3I , VK-
OMEGA , VK-OMEGA-PLUS , VKL , ADS-420 , LOAD CELLS TCA , TCE , SW ,
LCA , LCK , BPP , BPP-CB , BPP-LR , BPH , SENSORES SW-GAMA , SW-
OMEGA , SW-OMEGA PLUS , CABIN DISPLAY MB , EQUIPOS VK-3 , VK-2T ,
VK-2C , VK-3I , VK-OMEGA , VK-OMEGA-PLUS , VKL , ADS-420 , LOAD
CELLS TCA , TCE , SW , LCA , LCK , BPP , BPP-CB , BPP-LR , BPH , SEN-
SORES SW-GAMA , SW-OMEGA , SW-OMEGA PLUS , CABIN DISPLAY MB ,
EQUIPOS VK-3 , VK-2T , VK-2C , VK-3I , VK-OMEGA , VK-OMEGA-PLUS ,
VKL , ADS-420 , LOAD CELLS TCA , TCE , SW , LCA , LCK , BPP , BPP-CB ,
BPP-LR , BPH , SENSORES SW-GAMA , SW-OMEGA , SW-OMEGA PLUS ,
CABIN DISPLAY MB , EQUIPOS VK-3 , VK-2T , VK-2C , VK-3I , VK-OMEGA
PLUS , VKL , ADS-420 , LOAD CELLS TCA , TCE , SW , LCA , LCK , BPP ,
BPP-CB , BPP-LR , BPH , SENSORES SW-GAMA , SW-OMEGA , SW-OMEGA
PLUS , CABIN DISPLAY MB , EQUIPOS VK-3 , VK-2T , VK-2C , VK-3I , VK-
OMEGA , VK-OMEGA-PLUS , VKL , ADS-420 , LOAD CELLS TCA , TCE , SW ,
LCA , LCK , BPP , BPP-CB , BPP-LR , BPH , SENSORES SW-GAMA , SW-
OMEGA , SW-OMEGA PLUS , CABIN DISPLAY MB , EQUIPOS VK-3 , VK-2T ,
VK-2C , VK-3I , VK-OMEGA , VK-OMEGA-PLUS , VKL , ADS-420 , LOAD
CELLS TCA , TCE , SW , LCA , LCK , BPP , BPP-CB , BPP-LR , BPH , SEN-
SORES SW-GAMA , SW-OMEGA , SW-OMEGA PLUS , CABIN DISPLAY MB ,
EQUIPOS VK-3 , VK-2T , VK-2C , VK-3I , VK-OMEGA , VK-OMEGA-PLUS ,
VKL , ADS-420 , LOAD CELLS TCA , TCE , SW , LCA , LCK , BPP , BPP-CB ,
BPP-LR , BPH , SENSORES SW-GAMA , SW-OMEGA , SW-OMEGA PLUS ,
CABIN DISPLAY MB , EQUIPOS VK-3 , VK-2T , VK-2C , VK-3I , VK-OMEGA
PLUS , VKL , ADS-420 , LOAD CELLS TCA , TCE , SW , LCA , LCK , BPP ,
BPP-CB , BPP-LR , BPH , SENSORES SW-GAMA , SW-OMEGA , SW-OMEGA
PLUS , CABIN DISPLAY MB , EQUIPOS VK-3 , VK-2T , VK-2C , VK-3I , VK-
OMEGA , VK-OMEGA-PLUS , VKL , ADS-420 , LOAD CELLS TCA , TCE , SW ,
LCA , LCK , BPP , BPP-CB , BPP-LR , BPH , SENSORES SW-GAMA , SW-
OMEGA , SW-OMEGA PLUS , CABIN DISPLAY MB , EQUIPOS VK-3 , VK-2T ,
VK-2C , VK-3I , VK-OMEGA , VK-OMEGA-PLUS , VKL , ADS-420 , LOAD
CELLS TCA , TCE , SW , LCA , LCK , BPP , BPP-CB , BPP-LR , BPH , SEN-
SORES SW-GAMA , SW-OMEGA , SW-OMEGA PLUS , CABIN DISPLAY MB ,
EQUIPOS VK-3 , VK-2T , VK-2C , VK-3I , VK-OMEGA , VK-OMEGA-PLUS ,
VKL , ADS-420 , LOAD CELLS TCA , TCE , SW , LCA , LCK , BPP , BPP-CB ,
BPP-LR , BPH , SENSORES SW-GAMA , SW-OMEGA , SW-OMEGA PLUS ,
CABIN DISPLAY MB , EQUIPOS VK-3 , VK-2T , VK-2C , VK-3I , VK-OMEGA
PLUS , VKL , ADS-420 , LOAD CELLS TCA , TCE , SW , LCA , LCK , BPP ,
BPP-CB , BPP-LR , BPH , SENSORES SW-GAMA , SW-OMEGA , SW-OMEGA
PLUS , CABIN DISPLAY MB , EQUIPOS VK-3 , VK-2T , VK-2C , VK-3I , VK-
OMEGA , VK-OMEGA-PLUS , VKL , ADS-420 , LOAD CELLS TCA , TCE , SW ,
LCA , LCK , BPP , BPP-CB , BPP-LR , BPH , SENSORES SW-GAMA , SW-
OMEGA , SW-OMEGA PLUS , CABIN DISPLAY MB , EQUIPOS VK-3 , VK-2T ,
VK-2C , VK-3I , VK-OMEGA , VK-OMEGA-PLUS , VKL , ADS-420 , LOAD